

**WHAT IS CLAIMED IS:**

1. A microphone unit comprising:

an electret capacitor having first and second electrodes;

an amplifier with which voltage generated between said first and second electrodes of said electret capacitor is amplified and then outputted; and

a capacitor having a first electrode to which the output of said amplifier is applied, and a second electrode connected to said first electrode of said electret capacitor.

2. The microphone unit according to claim 1, wherein said amplifier comprises:

a first transistor having a first current electrode, a second current electrode connected to said second electrode of said electret capacitor, and a control electrode connected to said first electrode of said electret capacitor;

a current source connected to said first current electrode of said first transistor;

and

an inverting amplifier having an input terminal connected to said first current electrode of said first transistor.

3. The microphone unit according to claim 2, wherein said inverting amplifier comprises:

a first resistor having a first terminal connected to said first current electrode of said first transistor, and a second terminal;

a first operational amplifier having a negative input terminal connected to said second terminal of said first resistor, a positive input terminal to which a first fixed

00227056502960

potential is applied, and an output terminal; and

a second resistor having a first terminal connected to said negative input terminal of said first operational amplifier, and a second terminal connected to said output terminal of said first operational amplifier.

5

4. The microphone unit according to claim 2, wherein said current source is a second transistor having a first current electrode to which a second fixed potential is applied, a second current electrode connected to said first current electrode of said first transistor, and a control electrode to which a third fixed potential is applied.

10

5. The microphone unit according to claim 2, wherein said amplifier further comprises a voltage follower having an input terminal connected to said first current electrode of said first transistor, and an output terminal connected to said input terminal of said inverting amplifier.

15

6. The microphone unit according to claim 2 further comprising:

a first diode having a cathode and an anode connected to said first and second electrodes of said electret capacitor, respectively;

a second diode having an anode and a cathode connected to said first and

20 second electrodes of said electret capacitor, respectively; and

a third resistor connected in parallel with said electret capacitor.

7. A microphone unit comprising:

a semiconductor substrate to which a fixed potential is applied;

an insulting layer disposed above said semiconductor substrate;

25

09620595-072000

May 31/400  
Pr 301  
PST

an electret capacitor having a first electrode disposed above said insulating layer, and a second electrode that is free to oscillate and spaced apart from said first electrode;

an amplifier with which voltage generated between said first and second electrodes of said electret capacitor is amplified and then outputted; and

a conductive layer to which the output of said amplifier is applied, said conductive layer facing said first electrode of said electret capacitor and being disposed below said insulating layer.

8. The microphone unit according to claim 7, wherein said conductive layer is an impurity layer formed in the surface of said semiconductor substrate beneath said insulating layer.

9. The microphone unit according to claim 8 further comprising a wiring layer that is disposed above said insulating layer, and extends through said insulating layer to make contact with said conductive layer.

10. The microphone unit according to claim 7, wherein,  
said insulating layer has a first insulating film overlying said semiconductor substrate, and a second insulating film overlying said first insulating film, and  
said conductive layer is a wiring layer disposed above said first insulating film and below said second insulating film.

11. The microphone unit according to claim 7, wherein said amplifier comprises:

09620595-072000



comprises a voltage follower having an input terminal connected to said first current electrode of said first transistor, and an output terminal connected to said input terminal of said inverting amplifier.

5           15. The microphone unit according to claim 11 further comprising:

a first diode having a cathode and an anode connected to said first and second electrodes of said electret capacitor, respectively;

a second diode having an anode and a cathode connected to said first and second electrodes of said electret capacitor, respectively; and

10           a third resistor connected in parallel with said electret capacitor.

09620595-072000